

# Meteor<sup>MM</sup>



**One-touch secure transfer of data direct to CD & DVD.**

Supports popular memory formats & USB storage

Standalone – no PC required

Simple operation



The Meteor MultiMedia PowerTower professional duplicator offers fast, efficient backup of your important data from erasable memory cards or flash drives to archival CDs and DVDs at a cost effective price. Available with up to 3 target drives, Meteor<sup>MM</sup> PowerTower copiers are perfect for data-sensitive disc production with no PC intervention for minimum security risks.

With no PC or hard drive required the Meteor<sup>MM</sup> offers a secure and reliable duplication service. A compact and stylish design coupled with multiple memory card and USB drive readers built-in makes the Meteor<sup>MM</sup> the ultimate multi-functional disc duplicator.

Fitted with the latest DVD±R drives, up to 3 CDs discs can be created simultaneously in less than 3 minutes and 3 DVDs in less than 7 minutes.

Intelligent Multi-Session and Disc Spanning Technologies make data transfer as easy as one touch of a button.

Rigorously tested for performance and reliability, Meteor PowerTowers are manufactured to strict quality control standards, delivering enhanced duplication at every level.



Function:

Multimedia CD/DVD Duplication System

Supported Source Formats:

**MS Slot:** MS, MS-Duo, MS Pro, MS Pro Duo, MS MagicGate, MS Pro MagicGate, MS-Duo MagicGate, MS Pro Duo MagicGate etc.

**CF Slot:** CF I, CF II, IBM Micro Drive

**SD Slot:** SD, SD Pro, Mini SD\*, Mini SD Pro\*, Micro SD\*, SD HS, Wi-Fi SD, Super HS SD (\*Adaptor Required)

**MMC Slot:** MMC, MMC Pro, MMC II, RS-MMC

**Discs:** DVD-ROM, DVD-Video, DVD±R/RW, DVD±DL, CD-ROM, CD-I, Audio CD, Video CD, Bootable CD, Mixed-mode CD, Multi-session CD, CD-Plus, Business Card CD, Mini CD-R

Media Handling:

DVD±R/RW, DVD+R DL, CD-R/RW, Business card CD, 3" Mini CD-R

Targets:

Up to 3 targets

Drives:

(up to) 3x DVD±R, 1x DVD-ROM

Maximum Write Speeds:

18x DVD±R/48xCD-R

Voltage:

115V or 230V

Operating Temperature:

41°F ~ 104°F

Operating Humidity:

20% ~ 80%

Regulations:

FCC, CE, UL, RoHS

Operation:

No PC Required



## Warranty

12 months back to base, all parts and labour included.  
2<sup>nd</sup> year excludes drives and carriage.  
Extended warranties also available.



Verity Systems maintains a policy of continuous improvement and reserves the right to amend this specification without notice.

web: [www.veritysystems.com](http://www.veritysystems.com)

email: [sales@veritysystems.com](mailto:sales@veritysystems.com)

tel: +44 (0) 1252 317000

fax: +44 (0) 1252 316555